



LAMININ
COATINGS

for the next
generation

TECHNICAL DATA

EggShell

Smooth satin eggshell.

Date: February 2017/1

| | |
|---|--|
| Product code: LEG001 | GENERAL PREPARATIONS <ul style="list-style-type: none">° All surfaces must be clean, sound and dry.° Remove all loose flakes and apply PlasterSeal / PlasterPrime / WallPrime or BondAll, to obtain a stable surface.° Smooth out imperfections with Skim and repair cracks with Fill. To stabilize chalky surfaces, apply PlasterSeal / PlasterPrime / WallPrime or BondAll,° Previously painted sound surfaces can be washed with sugar soap and rinse thoroughly with clean water.° To ease application, sand previously painted stable surfaces.° For water damaged, porous and alkaline surfaces, apply WallPrime / PlasterPrime / BondAll or DampCure, to stabilize surface.° Remove rust from mild steel and galvanize substartes. Apply HydroEtch /AllPrime, to stabilize surface. If rust cannot be removed completely, spot prime with arust converter before applying HydroEtch /AllPrime. |
| Colour: White, Pastel, Deep, Clear | |
| Shelf life: 12 Months Packaging: 1ℓ, 5ℓ, 20ℓ Storage conditions: Store in a cool/dry place Stirring method: Stir with a flat paddle | FEATURES <p>EggShell dries to a tough and highly durable smooth satin finish. It is block and stain resistant with excellent flow and levelling properties. For interior use only.</p> WHERE TO USE <p>Walls, kitchens, bathrooms, mild steel, galvanized steel and wood.</p> |
| Flashpoint: Flammable | |
| Viscosity: 70 - 80 KU (at 23°C) Specific weight: 1.24- 1.34 Solids per volume: 42 - 53 % (Approx.) Solids per mass: 60 - 65 % (Approx.) Spreading rate: 10m ² /1ℓ/coat Dry film thickness 40µm (Recommended) Wet film thickness 100µm | |
| Recommended coats: 2 | |
| Drying time: Touch Dry: 4h @ 23°C Dry to handle: 16h @ 23°C Overcoating: Minimum 8 hours @ 23°C | |
| Application: Brush, roller and airless spray | |
| Cleaning: Mineral Turpentine | |
| | |
| | |
| | |
| | |



LAMININ COATINGS PTY LTD | reg no 2012/103111/07

13 MONUMENT ROAD | DRANJESIG | BLOEMFONTEIN 9301

T 051 447 8938 | F 051 447 8938

info@laminincoatings.co.za | www.laminincoatings.co.za

PRECAUTIONS

- ° Avoid painting in moist / humid conditions. To allow applied paint to cure, there should be no rain forecast for at least 7 days.
- ° Do not paint over surfaces with moisture content above 15%. Ideal level 5% or less
- ° Stir paint well with a flat paddle.
- ° Ideal application conditions and surface temperature should be between 10°C - 35°C with a relative humidity of less than 75%. It is not recommended to paint in direct sunlight as this will result in the paint drying too fast leading to visible "lap-marks". Windy conditions might have a similar effect and can cause a deposit of dust particles on the wet paint.
- ° To ensure colour- and sheen level consistency, purchase from the same production batch of paint.
- ° Tint bases contain fewer litres than advertised.
- ° Spreading rates are theoretical and based on smooth / flat surfaces.
- ° Do not wash or abrade newly painted surfaces until properly cured.
- ° Allow 7 days for paint to dry properly and 30 days to reach full strength.
- ° Store paint in a cool, dry place.

HEALTH & SAFETY

- ° Keep out of children's reach.
- ° Do not eat, drink or smoke during any application.
- ° Ensure appropriate ventilation during application and drying.
- ° May be harmful if swallowed.
- ° Wear protective equipment during preparation, application and cleaning.
- ° Avoid contact with eyes.
- ° In case of contact, seek medical advice.
- ° Avoid contact with skin. In case of contact, wash thoroughly with appropriate solvent.
- ° If skin irritation occurs, seek medical advice.

Disclaimer:

- * Specifications and recommendations are given in good faith and are meant to be used as a guideline.
- * All information is based on results obtained from our tests done and experience gained over time.
- * Application method and - equipment, condition of substrate and - during application, will have an influence on results. This is beyond the manufacturer's control.
- * As technology may change over time, please ensure the use of the latest Technical Data Sheet.
- * All information listed is owned or used under licence of Laminin Coatings (Pty) Ltd and its related affiliates. © 2013 Laminin Coatings (Pty) Ltd. All rights reserved.