



**LAMININ**  
COATINGS

for the next  
generation

## TECHNICAL DATA

<b>KladAll</b>	
Fibre reinforced waterproofing medium sheen acrylic.	
Date: February 2017/1	

<p><b>Product code:</b> LKA001</p> <p><b>Colour:</b> White, Pastel, Deep, Clear</p> <hr/> <p><b>Shelf life:</b> 12 Months <b>Packaging:</b> 1ℓ, 5ℓ, 20ℓ <b>Storage conditions:</b> Store in a cool/dry place <b>Stirring method:</b> Stir with a flat paddle</p> <hr/> <p><b>Flashpoint:</b> Non-flammable</p> <p><b>Viscosity:</b> 105 - 115 KU (at 23°C) <b>Specific weight:</b> 1.17 - 1.25 <b>Solids per volume:</b> 35 - 38 % (Approx.) <b>Solids per mass:</b> 46 - 48 % (Approx.) <b>Spreading rate:</b> 10m<sup>2</sup>/1ℓ/coat <b>Dry film thickness:</b> 30-40µm(Recommended) <b>Wet film thickness:</b> 100µm <b>VOC level:</b> ±15-18g/1ℓ White (Low VOC)</p> <p>VOC Level will increase if not tinted with glycol free colourants.</p> <p><b>Recommended coats:</b> 2</p> <hr/> <p><b>Drying time:</b> Touch Dry: 30min @ 23°C Dry to handle: 2h @ 23°C <b>Overcoating:</b> Minimum 2 hours @ 23°C</p> <hr/> <p><b>Application:</b> Brush or Roller</p> <p><b>Cleaning:</b> Water</p>	<p><b>GENERAL PREPARATIONS</b></p> <ul style="list-style-type: none"><li>◦ All surfaces must be clean, sound and dry.</li><li>◦ Remove all loose flakes and apply <b>PlasterSeal / PlasterPrime / WallPrime</b> or <b>BondAll</b>, to obtain a stable surface.</li><li>◦ Smooth out imperfections with <b>Skim</b> and repair cracks with <b>Fill</b>. To stabilize chalky surfaces, apply <b>PlasterSeal / PlasterPrime / WallPrime</b> or <b>BondAll</b>,</li><li>◦ Previously painted sound surfaces can be washed with sugar soap and rinse thoroughly with clean water.</li><li>◦ To ease application, sand previously painted stable surfaces.</li><li>◦ For water damaged, porous and alkaline surfaces, apply <b>WallPrime / PlasterPrime / BondAll</b> or <b>DampCure /</b>, to stabilize surface.</li></ul> <p><b>FEATURES</b></p> <p>KladAll is a fibre-reinforced pure acrylic waterproof coating that dries to a smooth stain resistant and washable medium-sheen finish, ideal for exterior use. It is UV-resistant, highly flexible, bridge hairline cracks and hides minor imperfections. KladAll's excellent waterproofing properties, anti mould- and fungal technology, makes it ideal for coastal conditions.</p> <p><b>WHERE TO USE</b></p> <p>Walls and eaves ceilings. Specially formulated for coastal conditions.</p>
--	--



LAMININ COATINGS PTY LTD | reg no 2012/103111/07

13 MONUMENT ROAD | ORANJESIG | BLOEMFONTEIN 9301

T 051 447 8938 | F 051 447 8938

info@laminincoatings.co.za | www.laminincoatings.co.za

**QUALITY GUARANTEE: 15 Years**

To qualify for quality guarantee, please register via our website or through your nearest distributor.

( Terms and conditions apply – please consult the webpage for further information: [www.laminincoatings.co.za](http://www.laminincoatings.co.za) )

**PRECAUTIONS**

- Avoid painting in moist / humid conditions. To allow applied paint to cure, there should be no rain forecast for at least 7 days.
- Do not paint over surfaces with moisture content above 15%. Ideal level 5% or less
- Stir paint well with a flat paddle.
- Ideal application conditions and surface temperature should be between 10°C - 35°C with a relative humidity of less than 75%. It is not recommended to paint in direct sunlight as this will result in the paint drying too fast leading to visible "lap-marks". Windy conditions might have a similar effect and can cause a deposit of dust particles on the wet paint.
- To ensure colour- and sheen level consistency, purchase from the same production batch of paint.
- Tint bases contain fewer litres than advertised.
- Spreading rates are theoretical and based on smooth / flat surfaces.
- Do not wash or abrade newly painted surfaces until properly cured.
- Allow 7 days for paint to dry properly and 30 days to reach full strength.
- Store paint in a cool, dry place.

**HEALTH & SAFETY**

- Keep out of children's reach.
- Do not eat, drink or smoke during any application.
- Ensure appropriate ventilation during application and drying.
- May be harmful if swallowed.
- Wear protective equipment during preparation, application and cleaning.
- Avoid contact with eyes.
- In case of contact, seek medical advice.
- Avoid contact with skin. In case of contact, wash thoroughly with appropriate solvent.
- If skin irritation occurs, seek medical advice.

**Disclaimer:**

- \* Specifications and recommendations are given in good faith and are meant to be used as a guideline.
- \* All information is based on results obtained from our tests done and experience gained over time.
- \* Application method and - equipment, condition of substrate and - during application, will have an influence on results. This is beyond the manufacturer's control.
- \* As technology may change over time, please ensure the use of the latest Technical Data Sheet.
- \* All information listed is owned or used under licence of Laminin Coatings (Pty) Ltd and its related affiliates. © 2013 Laminin Coatings (Pty) Ltd. All rights reserved.