

Material safety data sheet

MATERIAL SAFETY DATA SHEET

PRODUCT: H2H EkoCoat
DATE PRINTED: 21/01/2025
PAGE 1 OF 4

1. PRODUCT AND COMPANY IDENTIFICATION (This page may be used as an emergency data sheet)

Company Details:

Name: Laminin Coatings (Pty) Ltd
Address: 109 Fritz Stockenström Street, East End, BFN
Tel.: 051 – 447 8938
Fax: 086 518 6455

Product Details:

| | | | |
|------------------|----------------------------|---------------|---------------|
| Trade Name: | H2H EkoCoat | CAS No.: | Mixture |
| Main use: | Industrial or domestic use | Hazchem Code: | Not available |
| Chemical family: | Alkyd Paint | UN No.: | Not available |
| Chemical Name: | Solvent based paint | | |

2. COMPOSITION

Solvent based alkyd paint
Hazardous Components: Classified as hazardous

3. HAZARDS IDENTIFICATION

| | |
|------------------------|------------------------|
| Main Hazard: | Flammable |
| Flammability: | Yes – flammable liquid |
| Chemical Hazard: | Yes |
| Biological Hazard: | Not hazardous |
| Reproductive Hazard: | None |
| Health effects – Eyes: | Yes |
| Skin: | Yes |
| Ingestion: | Yes |
| Inhalation: | Yes |
| Carcinogenicity: | None |
| Mutagenicity: | None |
| Neurotoxicity: | None |



LAMININ COATINGS (PTY) LTD • Reg No 2012/103111/07


109 FRITZ STOCKENSTROM ST | NEW EAST END | BLOEMFONTEIN 9301



www.laminincoatings.co.za



SINCE 1981



Material safety data sheet

MATERIAL SAFETY DATA SHEET

PRODUCT: H2H EkoCoat
DATE PRINTED: 21/01/2025
PAGE 2 OF 4

4. FIRST AID MEASURES

| | |
|-----------------------|---|
| In contact with eyes: | Wash with lukewarm water for several minutes while holding eyelids open or until irritation subsides and seek medical advice. |
| In contact with skin: | Wash with white spirits before the solution dries and remove any contaminated clothing and wash with large amounts of soap and water. If irritation persists seek medical advice. |
| If ingested: | May cause nausea. Do not induce vomiting. Drink as much water as possible and seek medical advice immediately. |
| If inhaled: | Remove to well-ventilated area. In severe cases seek medical advice. |
| Other precautions: | Avoid prolonged contact with skin. |

5. FIRE FIGHTING MEASURES

| | |
|----------------------|---|
| Extinguishing media: | Water, carbon dioxide or dry chemicals |
| Special hazards: | This product is solvent based and is flammable. Dry resin will burn producing carbon dioxide and sometimes oxides of nitrogen accompanied by dense black smoke. |
| Protective clothing: | Protective clothing and a self-contained breathing apparatus |

6. ACCIDENTAL RELEASE MEASURES

| | |
|----------------------------|--|
| Personal precautions: | Protective gloves. Overalls and footwear. Respiratory equipment if in an enclosed area. Eliminate all ignition sources |
| Environmental precautions: | Do not wash into drains unless leading to a suitable effluent process. |
| Small spills: | Absorb with sand or rags before the paint is allowed to dry. |
| Large spills: | Contain and pump into a receiving vessel for removal. |
| Waste disposal: | Check with Federal, Provincial and local Government regulations and requirements for disposal. |

7. HANDLING AND STORAGE

| | |
|--------------------|--|
| Suitable material: | Steel containers. |
| Handling: | Wear protective gloves, goggles, overalls and apron Observe good housekeeping practice. Keep workplace well ventilated |
| Storage: | Store under cover at temperatures above freezing and out of direct sunlight. Containers should be properly sealed. Open in ventilated surroundings as small levels of VOC may accumulate in top void of the containers. Stir before use! Keep out of reach of children. |

8. EXPOSURE CONTROL / PERSONAL PROTECTION

| | |
|------------------------------------|---|
| Occupational exposure limits: | Not applicable |
| Engineering control measures: | Use mechanical ventilation to reduce exposure. |
| Personal protection – respiratory: | Breathing apparatus if ventilation is not adequate |
| Personal protection – eye: | Safety goggles are recommended |
| Personal protection – skin: | Safety goggles, waterproof overalls and boots are recommended in cases of severe splashing. |
| Other protection: | Do not eat drink or smoke when handling the product. |



LAMININ COATINGS (PTY) LTD • Reg No 2012/10311/07


109 FRITZ STOCKENSTROM ST | NEW EAST END | BLOEMFONTEIN 9301



www.laminincoatings.co.za



SINCE 1981



Material safety data sheet

MATERIAL SAFETY DATA SHEET

PRODUCT: H2H EkoCoat
DATE PRINTED: 21/01/2025
PAGE 3 OF 4

9. PHYSICAL and CHEMICAL PROPERTIES

| | |
|-----------------------|--|
| Physical State: | Liquid |
| Appearance: | White / Coloured pourable liquid |
| Odour: | Characteristic |
| pH: | Not applicable |
| Boiling point: | 100°C (as for Water) |
| Flash point: | Combustible |
| Explosive properties: | Not applicable |
| Vapour pressure: | Heavier than air |
| Density: | 1.35 – 1.45 (as supplied) |
| Solubility – water: | Not soluble |
| Solubility – solvent: | Soluble in some alcohols, esters and aromatic and aliphatic solvents |

10. STABILITY and REACTIVITY

| | |
|-----------------------------------|---|
| Stability: | Stable under recommended conditions of storage. |
| Incompatible materials: | Not available |
| Conditions to void: | Extremes temperatures in closed containers / sparks and open flames |
| Hazardous decomposition products: | None |
| Hazardous reactions: | None / Will not occur |

11. TOXICOLOGICAL INFORMATION

| | |
|---------------------------|---|
| Acute Toxicity: | Long term experience of handling this class of product under industrial conditions indicate the absence of chronic or acute effects. |
| Skin and eye contact: | |
| Acute / Chronic Toxicity: | Aliphatic Solvents: Has been known to cause Dermatitis or kidney damage. It can also cause a headache or coordination problems. White spirits has been known to cause Dermatitis, conjunctivitis, corneal damage, nausea, vomiting, diarrhoea, headache and dizziness. |
| Carcinogenicity: | None known |
| Mutagenicity: | None known |
| Neurotoxicity: | None known |
| Reproductive hazards: | None known |

12. ECOLOGICAL INFORMATION

| | |
|-----------------------------|--|
| Aquatic toxicity – fish: | high toxicity |
| Aquatic toxicity – daphnia: | none known |
| Aquatic toxicity – algae: | none known |
| Biodegradability: | The base polymer is slowly biodegraded |

13. DISPOSAL CONSIDERATIONS

Disposal of product and packaging should always comply with local and national regulations.
Recover liquid with absorbent material. Disposal methods: Waste product should not be discharged directly into drains or waterways without treatment. Waste water containing product should be treated in a separation and biological treatment plant.
Disposal of packaging: Containers may be cleaned and returned to the supplier for re-use.



LAMININ COATINGS (PTY) LTD • Reg No 2012/103111/07


109 FRITZ STOCKENSTROM ST | NEW EAST END | BLOEMFONTEIN 9301



www.laminincoatings.co.za



SINCE 1981



Material safety data sheet

MATERIAL SAFETY DATA SHEET

PRODUCT: H2H EkoCoat
DATE PRINTED: 21/01/2025
PAGE 4 OF 4

14. TRANSPORT INFORMATION

NOT CLASSIFIED AS HAZARDOUS FOR TRANSPORT.

15. REGULATORY INFORMATION

EEC hazard classification: None
This product contains only substances which are on the European Inventory of Existing Chemicals (EINECS)

16. OTHER INFORMATION

The information provided in this Material Safety Data Sheet is based on the present state of our knowledge. This data is intended to enable safety assessments to be made and should not be construed as guaranteeing specific properties. Users are recommended to consult technical information sheets for advice on specific applications. The material may be used under conditions over which Laminin Paints has no control or in ways we cannot anticipate, we give no warranty, expressed or implied, as to the accuracy of the information and assume no responsibility for any damages that may occur.

Further information may be obtained from:

See above.:



LAMININ COATINGS (PTY) LTD • Reg No 2012/103111/07

109 FRITZ STOCKENSTROM ST | NEW EAST END | BLOEMFONTEIN 9301



www.laminincoatings.co.za



SINCE 1981